

# Product data sheet

Specifications



## APC Back-UPS 600VA, 120V, 1 USB charging port, 7 NEMA outlets (2 surge)

BE600M1

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	330 W
Rated power in VA	600 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
output connection type	5 NEMA 5-15R 2 NEMA 5-15R surge
Cable length	1.5 m
Battery type	Lead-acid battery
Provided equipment	User manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	10 h
Number of battery replacement quantity	1
Battery charger power	7 W rated
Battery power in VAH	78 VAh capacity 66 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC154</a>
Extended runtime	0

### General

Number of power module free slots	0
Number of power module filled slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Redundant	No
-----------	----

## Physical

Height	13.9 cm
Width	27.4 cm
Depth	10.5 cm
net weight	3.49 kg
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	92...139 V

## Output

Maximum configurable power in W	330 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	600 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	California Energy Commission (CEC) cTUVus NOM
Equipment protection policy	Lifetime : \$75000

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...90 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	35 dBA
heat dissipation	16 Btu/h

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

## Surge Protection and Filtering

Surge energy rate	490 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Let through voltage rating	5 V

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.6 cm
Package 1 Width	16.8 cm
Package 1 Length	36.3 cm
Package 1 Weight	3.81 kg
SCC14	10731304325113

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)

California Proposition 65   **WARNING:** This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)