

# Product data sheet

Specifications



## APC Power-Saving Back-UPS ES 700VA, 230V, 8 Outlets, CEE, 7/5

BE700G-CP

⚠ Discontinued on: Sep 28, 2021

⚠ End-of-service on: Dec 31, 2021

⚠ Discontinued - Service only

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	405 W
Rated Power In Va	700 VA
Input Connection Type	French/Belgian
Nb Of Power Socket Outlets	4 French/Belgian 4 French/Belgian surge
Cable Length	1.83 m
Battery Type	Lead-acid battery
Provided Equipment	CD with software Telephone cable User manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	16 h
Battery Voltage	12 V
Battery Capacity	9.0 Ah
Battery Charger Power	5 W rated
Battery Power In Vah	86 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	<a href="#">RBC17</a>
Extended Runtime	0

### General

Max Runtime 7 min

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

## Physical

Colour	Black
Height	8.9 cm
Width	22.4 cm
Depth	31.1 cm
Net Weight	6.93 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	Yes

## Input

Network Frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug Standard	French/Belgian
Maximum Input Current	10 A

## Output

Maximum Configurable Power In W	405 W
Output Frequency	47...63 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Ups Type	Standby
Wave Type	Stepped approximation to a sinewave
Output Voltage Tolerance	+/- 5% static and 100% load step
Maximum Configurable Power In Va	700 VA
Transfer Time	6 ms typical : 10 ms maximum

## Conformance

Product Certifications	CE
Equipment Protection Policy	Lifetime : 100000 euros

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...30000 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...9144.00 m
Acoustic Level	40 dBA

# Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

# Surge Protection and Filtering

Surge Energy Rate	310 J
Noise Suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	RJ11 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100 base-T Ethernet

# Packing Units

Package 1 Height	12.7 cm
Package 1 Width	27.9 cm
Package 1 Length	40 cm
Package 1 Weight	7.84 kg
Number Of Units In Package 2	2
Package 2 Length	323.85 mm
Package 2 Weight	16.33 kg
Number Of Units In Package 3	48
Package 3 Length	121.92 cm
Package 3 Weight	636.36 kg
Scc14	10731304271731
Pallet Unit Layers	20
Pallet Layers	4

# Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

## Sustainability

**Green Premium™** label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient   Take-back

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant  
[EU RoHS Declaration](#)

Weee   The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins