

# Product data sheet

Specifications



## APC Power-Saving Back-UPS ES 700VA, 230V, 8 Outlets, CEE, 7/7

BE700G-GR

 **Discontinued on:** Jul 18, 2023

 **Discontinued**




### Overview

Lead time                      Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	405 W
Rated power in VA	700 VA
Input Connection Type	Schuko CEE 7/7P
output connection type	4 Schuko CEE 7 4 Schuko CEE 7 surge
Cable length	1.8 m
Battery type	Lead-acid battery
Provided equipment	CD with software Telephone cable User manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a> 
Efficiency	<a href="#">View Efficiency Graph</a> 
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	12 V
Battery capacity	9.0 Ah
Battery charger power	5 W rated
Battery power in VAh	86 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">RBC17</a> 
Extended runtime	0

### General

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Max runtime	7 min
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Colour	Black
Height	8.9 cm
Width	22.4 cm
Depth	31.1 cm
net weight	6.93 kg
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	180...266 V
Maximum input current	10 A
Switching current capacity	10 A

## Output

Maximum configurable power in W	405 W
Output frequency	47...63 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Output voltage tolerance	+/- 5% static and 100% load step
Maximum configurable power in VA	700 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE
Equipment protection policy	Lifetime : 100000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %

Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	40 dBA

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

## Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.7 cm
Package 1 Width	40 cm
Package 1 Length	27.9 cm
Package 1 Weight	7.84 kg
SCC14	10731304271700
Pallet unit layers	20
Pallet layers	4

## Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Weee   The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile   [End of Life Information](#)