

# Product data sheet

Specifications



## APC Back-UPS 700VA, 230V, 4 India outlets (1 surge)

BE700Y-IND

⚠ Discontinued on: Feb 1, 2024

⚠ To be discontinued

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	420 W
Rated Power In Va	700 VA
Output Connection Type	3 India 3-pin 6A 1 India 3-pin 6A surge
Cable Length	1.00 m
Number Of Cables	1
Battery Type	Lead-acid battery

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	6 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	18 W rated
Battery Life	2...4 year(s)
Replacement Battery	<a href="#">BATT17-1209</a> <a href="#">RBC17</a>
Extended Runtime	0

### General

Provided Equipment	user manual USB cable warranty card
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Redundant	No
-----------	----

## Physical

Height	13 cm
Width	22 cm
Depth	29 cm
Net Weight	7.8 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	50 Hz +/- 3 Hz
Plug Standard	India 3-pin 6A

## Output

Maximum Configurable Power In W	420 W
Output Frequency	47...63 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Efficiency	95 % (full load)
Maximum Configurable Power In Va	700 VA

## Conformance

Product Certifications	BIS
------------------------	-----

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-5...45 °C
Storage Relative Humidity	0...95 %
Acoustic Level	45 dBA
Heat Dissipation	42.68 Btu/h

## Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge Energy Rate	160 J
Noise Suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	17 cm
Package 1 Width	41 cm
Package 1 Length	27 cm
Package 1 Weight	9 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)