

Product data sheet

Specifications



APC ES 750VA, 100V, 2 USB, 9 NEMA outlets (3 surge)

BE750M2-JP

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	100 V
Main Output Voltage	100 V
Rated Power In W	450 W
Rated Power In Va	750 VA
Input Connection Type	NEMA 5-15P
Output Connection Type	6 NEMA 5-15R 3 NEMA 5-15R surge
Cable Length	1.52 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual USB cable

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Battery Charger Power	10 W rated
Battery Power In Vah	84 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	RBC17J
Extended Runtime	0

General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	13.9 cm
Width	32.7 cm
Depth	10.5 cm
Net Weight	4.6 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Switching Current Capacity	15 A

Output

Maximum Configurable Power In W	450 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Standby
Wave Type	Stepped approximation to a sinewave
Maximum Configurable Power In Va	750 VA
Transfer Time	6 ms typical : 10 ms maximum

Conformance

Product Certifications	PSE
------------------------	-----

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...90 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0.00...15240.00 m
Acoustic Level	45 dBA

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control Panel	LED status display with on line : on battery : replace battery and building wiring fault

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	19.6 cm

Package 1 Width	16.8 cm
Package 1 Length	41.6 cm
Package 1 Weight	5.25 kg
Scc14	10731304325427
Pallet Unit Layers	10
Pallet Layers	6

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Lead Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)