

# Product data sheet

Specifications



## APC Back-UPS CS 350VA, 230V

BK350-RS

⚠ Discontinued on: Sep 20, 2021

⚠ End-of-service on: Dec 31, 2021

⚠ Discontinued

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	210 W
Rated Power In Va	350 VA
Input Connection Type	IEC 60320 C14
Nb Of Power Socket Outlets	3 IEC 60320 C13 1 IEC 60320 C13 surge 2 IEC Jumpers
Battery Type	Lead-acid battery
Provided Equipment	CD with software User manual USB cable

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	6 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	14 W rated
Battery Power In Vah	86 VAh runtime
Battery Life	4...6 year(s)
Replacement Battery	<a href="#">RBC2</a>
Extended Runtime	0

### General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Redundant	No
-----------	----

## Physical

Colour	Beige
Height	16.5 cm
Width	9.1 cm
Depth	28.4 cm
Net Weight	5.91 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	50/60 Hz +/- 5 Hz manual switch
Input Voltage Limits	196...280 V

## Output

Maximum Configurable Power In W	210 W
Ups Type	Standby
Maximum Configurable Power In Va	350 VA
Transfer Time	4 ms typical : 8 ms maximum

## Conformance

Product Certifications	C-Tick CE GOST VDE
Standards	EN 50091-1 EN 50091-2

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	40 dBA
Heat Dissipation	19 Btu/h

## Communications & Management

Free Slots	0
------------	---

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge Energy Rate	300 J
Noise Suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	RJ11 modem/fax/DSL protection (two wire single line)

## Packing Units

Package 1 Height	17.8 cm
Package 1 Width	24.1 cm
Package 1 Length	36.8 cm
Package 1 Weight	6.82 kg
Scc14	10731304101465

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------