

Product data sheet

Specifications



APC Back-UPS 650VA, 220V, 4 chinese outlets

BK650-CH

⚠ Discontinued on: Mar 9, 2023

⚠ Discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V
Main Output Voltage	230 V
Rated Power In W	400 W
Rated Power In Va	650 VA
Input Connection Type	Australian/Chinese
Output Connection Type	4 chinese outlet
Cable Length	2.44 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software User manual USB cable

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	24 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	5 W rated
Battery Power In Vah	124 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	RBC2
Extended Runtime	0

General

Max Runtime 50 min

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Charcoal
Height	10.5 cm
Width	28.6 cm
Depth	17.1 cm
Net Weight	6.7 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	45...65 Hz
Plug Standard	Australian/Chinese
Input Voltage Limits	165...266 V

Output

Maximum Configurable Power In W	400 W
Output Frequency	47...63 Hz sync to mains
Crest Factor	3 : 1
Wave Type	Stepped approximation to a sinewave
Efficiency	95 % (full load)
Maximum Output Current	7 A
Maximum Configurable Power In Va	650 VA

Conformance

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	10...90 %
Operating Altitude	0...3333 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	5...95 %
Storage Altitude	0.00...4572.00 m

Acoustic Level	40 dBA
----------------	--------

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control Panel	LED Status display with on line : on battery

Surge Protection and Filtering

Surge Energy Rate	180 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	17.8 cm
Package 1 Length	38.1 cm
Package 1 Weight	7.5 kg
Scc14	10731304225666

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)