

Product data sheet

Specifications

APC Back-UPS Pro 1400VA, 120V



BP1400

 **Discontinued on:** Jun 14, 2022

 **Discontinued**

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	120 V
Rated Power In W	950 W
Rated Power In Va	1400 VA
Output Connection Type	6 NEMA 5-15R
Number Of Rack Unit	0U
Cable Length	1.83 m
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph 
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	5.7 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	68 W rated
Battery Life	3...5 year(s)
Replacement Battery	RBC7  SMT1500I-CH 
Extended Runtime	0

General

Provided Equipment	user manual
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Physical

Colour	Beige
Height	21.6 cm
Width	17 cm
Depth	43.9 cm
Net Weight	24.59 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	88...139 V

Output

Maximum Configurable Power In W	950 W
Ups Type	Line interactive
Maximum Output Current	15 A
Maximum Configurable Power In Va	1400 VA

Conformance

Product Certifications	CSA
Equipment Protection Policy	Lifetime : \$150000

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	50 dBA

Communications & Management

Free Slots	0
Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate	320 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------