

# Product data sheet

Specifications



## APC Back-UPS LS 700VA, 120V, Factory Serviced

BP700UC

 **Discontinued on:** Jun 10, 2022

 **Discontinued**



### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated Power In W	410 W
Rated Power In Va	700 VA
Input Connection Type	NEMA 5-15P
Nb Of Power Socket Outlets	4 NEMA 5-15R 3 NEMA 5-15R surge
Number Of Rack Unit	0U
Cable Length	1.83 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software User manual USB cable Cord management straps

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a> 
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	10 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	10 W rated
Battery Power In Vah	98 VAh runtime
Battery Life	4...6 year(s)
Replacement Battery	<a href="#">RBC17</a> 
Extended Runtime	0

### General

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

## Physical

Colour	Charcoal
Height	23.9 cm
Width	12.7 cm
Depth	20.1 cm
Net Weight	7.74 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	82...144 V adjustable 93...130 V

## Output

Maximum Configurable Power In W	410 W
Ups Type	Standby
Maximum Output Current	12 A
Maximum Configurable Power In Va	700 VA

## Conformance

Product Certifications	CSA
Standards	FCC part 68 UL 1778
Equipment Protection Policy	Lifetime : \$150000

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %

## Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge Energy Rate	510 J
-------------------	-------

Noise Suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	RJ11 modem/fax/DSL protection (four wire dual line)

## Packing Units

Package 1 Weight	8.64 kg
Package 1 Height	29 cm
Package 1 Width	21.3 cm
Package 1 Length	32.8 cm
Scc14	10731304104091
Number Of Units In Package 2	2
Number Of Units In Package 3	64

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™** label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient   Take-back

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant  
[EU RoHS Declaration](#)