

Product data sheet

Specifications



APC Back-UPS RS 1000VA, 230V

BR1000I

⚠ Discontinued on: Jun 10, 2022

⚠ Discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Rated Power In W	600 W
Rated Power In Va	1000 VA
Output Connection Type	6 IEC 60320 C13 2 IEC 60320 C13 surge
Number Of Rack Unit	2U
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	1
Number Of Battery Free Slots	0
Battery Recharge Time	15 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	11 W rated
Battery Life	4...6 year(s)
Replacement Battery	RBC32
Extended Runtime	0

General

Provided Equipment	CD with software cord management straps 2, detachable IEC C13 to IEC C14 power cords telephone cable user manual USB cable warranty card
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Physical

Colour	Beige
Height	37.1 cm
Width	8.6 cm
Depth	33.3 cm
Net Weight	10.61 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Usb Compatible	Yes

Input

Network Frequency	47...63 Hz
Input Voltage Limits	160...286 V adjustable 175...295 V

Output

Maximum Configurable Power In W	600 W
Ups Type	Line interactive
Maximum Output Current	10 A
Maximum Configurable Power In Va	1000 VA

Conformance

Product Certifications	A-Tick C-Tick CE GOST VDE
Equipment Protection Policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-5...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	45 dBA
Heat Dissipation	180 Btu/h

Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge Energy Rate	180 J
Noise Suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	RJ11 modem/fax/DSL protection (two wire single line)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	45.5 cm
Package 1 Width	20.3 cm
Package 1 Length	41.6 cm
Package 1 Weight	11.795 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------