

# Product data sheet

Specifications



## APC Back-UPS, 1100VA/660W, Tower, 230V, 5x 6A India outlets, AVR, User Replaceable Battery

BR1100CI-IN

⚠ Discontinued on: Jun 15, 2023

⚠ Discontinued

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V
Rated power in W	660 W
Rated power in VA	1100 VA
output connection type	3 India 2/3-pin 6A 2 India 2/3-pin 6A surge
Cable length	1.48 m
Number of cables	1
Battery type	Lead-acid battery

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	10 h
Number of battery replacement quantity	1
Battery charger power	18 W rated
Battery life	2...4 year(s)
Replacement battery	<a href="#">APCRBC113</a>
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

### General

Provided equipment	user manual warranty card
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Physical

Colour	Charcoal
Height	22.2 cm
Width	13.2 cm
Depth	35.6 cm
net weight	11 kg
Mounting preference	No preference
mounting mode	Not rack-mountable
USB compatible	No

## Input

Network frequency	47...63 Hz
Input voltage limits	160...286 V adjustable 175...295 V

## Output

Maximum configurable power in W	660 W
UPS type	Line interactive
Maximum output current	10 A
Maximum configurable power in VA	1100 VA

## Conformance

Product certifications	CE
------------------------	----

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-5...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	45 dBA
heat dissipation	180 Btu/h

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	441 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31 cm
Package 1 Width	45 cm
Package 1 Length	24.4 cm
Package 1 Weight	13.5 kg
SCC14	10731304250132

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)