

Product data sheet

Specifications



APC Back-UPS Pro, 1200VA/720W,
Tower, 230V, 6x French/Belgian
outlets, AVR, LCD, User
Replaceable Battery

BR1200G-FR

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Rated Power In W	720 W
Rated Power In Va	1200 VA
Output Connection Type	3 French/Belgian 3 French/Belgian surge
Cable Length	1.52 m
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Number Of Battery Replacement Quantity	1
Battery Voltage	24 V
Battery Capacity	9.0 Ah
Battery Charger Power	23 W rated
Battery Life	3...5 year(s)
Replacement Battery	APCRBC124
Battery Graph Comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended Runtime	0

General

Provided Equipment	telephone cable user manual USB cable
--------------------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Height	30.1 cm
Width	11.2 cm
Depth	38 cm
Net Weight	11.6 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug Standard	French/Belgian
Input Voltage Limits	156...300 V adjustable 176...294 V

Output

Maximum Configurable Power In W	720 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Maximum Configurable Power In Va	1200 VA
Transfer Time	10 ms typical : 12 ms maximum

Conformance

Product Certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment Protection Policy	Lifetime : 150000 euros

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...30000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	45 dBA

Communications & Management

Control Panel	Multifunction LCD status and control console
---------------	--

Surge Protection and Filtering

Surge Energy Rate	441 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	38.7 cm
Package 1 Width	23.8 cm
Package 1 Length	48.8 cm
Package 1 Weight	13.2 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	10
Package 2 Height	117 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	145.5 kg
Scc14	10731304268724

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information