

# Product data sheet

Specifications



APC Back-UPS Pro, 1200VA/720W,  
Tower, 230V, 6x CEE 7/7 Schuko  
outlets, AVR, LCD, User  
Replaceable Battery

BR1200G-GR

## Overview

Lead time	Usually in Stock
-----------	------------------

## Main

Main Input Voltage	230 V
Rated power in W	720 W
Rated power in VA	1200 VA
product or component type	Uninterruptible power supply (UPS)
output connection type	3 Schuko CEE 7 3 Schuko CEE 7 surge
Cable length	1.5 m

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	2
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery charger power	23 W rated
Extended runtime	0
Replacement battery	<a href="#">APCRBC124</a>

## General

Provided equipment	telephone cable user manual USB cable warranty card
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Physical

Height	30.1 cm
Width	11.2 cm
Depth	38.2 cm
net weight	13 kg
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50 Hz +/- 1 Hz 60 Hz +/- 1 Hz
Input voltage limits	156...300 V adjustable 176...294 V
Maximum input current	10 A
Switching current capacity	10 A

## Output

Maximum configurable power in W	720 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Bypass type	Built-in bypass
Maximum configurable power in VA	1200 VA
Transfer time	10 ms typical : 12 ms maximum

## Conformance

Product certifications	BSI 1363 CE NEMKO
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Acoustic level	45 dBA
----------------	--------

## Surge Protection and Filtering

Surge energy rate	441 J
Data line protection	RJ11 modem/fax/DSL protection (two wire single line)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39 cm
Package 1 Width	49 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.8 kg
SCC14	10731304286834

## Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	<a href="#">End of Life Information</a>