

Product data sheet

Specifications



APC Power-Saving Back-UPS Pro 1500, 1500VA, 230V, LCD, 6 India outlets (2 surge)

BR1500G-IN

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Rated Power In W	865 W
Rated Power In Va	1500 VA
Nb Of Power Socket Outlets	4 India 3-pin 6A 2 India 3-pin 6A surge
Cable Length	1.52 m
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	7.2 h
Number Of Battery Replacement Quantity	1
Additional Information	9Ah x 2 internal batteries
Battery Charger Power	30 W rated
Battery Power In Vah	216 VAh runtime
Battery Life	2...4 year(s)
Replacement Battery	APCRBC124 APCRBC144
Battery Option	BR24BPG-IN 1 432 VAh
Battery Graph Comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended Runtime	0

General

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Provided Equipment	telephone cable user manual USB cable warranty card
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Black
Height	30.1 cm
Width	11.4 cm
Depth	38.2 cm
Net Weight	11.76 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug Standard	India 3-pin 16A
Input Voltage Limits	170...294 V

Output

Maximum Configurable Power In W	865 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Waveform Type	Stepped approximation to a sinewave
Efficiency	85 % (full load) 86 % (half load)
Maximum Configurable Power In Va	1500 VA
Transfer Time	6 ms typical : 10 ms maximum

Conformance

Product Certifications	BIS
------------------------	-----

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %

Storage Altitude	0.00...15240.00 m
Acoustic Level	45 dBA

Communications & Management

Control Panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate	680 J
Let Through Voltage Rating	330 V

Packing Units

Package 1 Height	38.1 cm
Package 1 Width	22.9 cm
Package 1 Length	48.3 cm
Package 1 Weight	13.19 kg
Number Of Units In Package 2	2
Package 2 Height	9860.28 mm
Package 2 Width	12786.36 mm
Package 2 Length	12717.78 mm
Package 2 Weight	28.08 kg
Scc14	10731304268793

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products. **Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)