

Product data sheet

Specifications



APC Back-UPS 1500VA, 120V,
AVR, LCD, LAM, 2 USB charging
ports, 10 NEMA outlets (4 surge)

BR1500M2-LM

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V
Rated Power In W	900 W
Rated Power In Va	1500 VA
Nb Of Power Socket Outlets	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable Length	1.83 m
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	1
Number Of Battery Free Slots	0
Battery Recharge Time	16 h
Number Of Battery Replacement Quantity	2
Battery Charger Power	11 W rated
Battery Power In Vah	181 VAh capacity 181 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	APCRBC161
Extended Runtime	0

General

Provided Equipment	coaxial cable user manual USB cable
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Physical

Colour	Black
Height	26 cm
Width	10 cm
Depth	36.8 cm
Net Weight	12.5 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	88...147 V
Maximum Input Current	12 A
Switching Current Capacity	15 A

Output

Maximum Configurable Power In W	900 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Waveform Type	Stepped approximation to a sinewave
Maximum Configurable Power In Va	1500 VA
Transfer Time	8 ms typical : 10 ms maximum

Conformance

Product Certifications	NOM TUV C-US certified
Standards	FCC part 15 class B
Equipment Protection Policy	Lifetime : \$250000

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage Altitude	0.00...3048.00 m
Acoustic Level	45 dBA

Communications & Management

Control Panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge Energy Rate	1080 J
Noise Suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous
Data Line Protection	RJ45 10/100/1000 Base-T Ethernet protection Coaxial cable for CATV/SATV/modem/audio-video

Packing Units

Package 1 Height	38 cm
Package 1 Width	24.1 cm
Package 1 Length	50 cm
Package 1 Weight	14.2 kg
Number Of Units In Package 2	1
Package 2 Height	508.00 mm
Package 2 Width	228.60 mm
Package 2 Length	381.00 mm
Package 2 Weight	14.20 kg
Number Of Units In Package 3	16
Scc14	10731304337833

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)