

BR550G-AR

APC Back-UPS Pro, 550VA/330W, Tower,
230V, 6x AS3112 Australian outlets, AVR,
LCD, User Replaceable Battery



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Rated power in W	330 W
Rated power in VA	550 VA
Product or component type	Uninterruptible power supply (UPS)
Output connection type	3 Australian surge 3 Australian
Cable length	1.8 M
Battery type	Lead-acid battery

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	12 H
Number of battery replacement quantity	1
Battery charger power	5 W rated
Battery life	3...5 Year(S)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

General

Provided equipment	CD with software User manual USB cable warranty card
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	19 Cm
Width	9.1 Cm
Depth	31 Cm
Net weight	6.53 Kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	Australian/Chinese
Input voltage limits	176...282 V
Maximum input current	6 A
Switching current capacity	7 A

Output

Maximum configurable power in W	330 W
Output frequency	50 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	550 VA
Transfer time	4 ms typical : 8 ms maximum

Conformance

Product certifications	IRAM
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 M
Acoustic level	40 dBA

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm





Surge Protection and Filtering

Surge energy rate	420 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.2 Cm
Package 1 Width	44.2 Cm
Package 1 Length	13.8 Cm
Package 1 Weight	7.71 Kg
SCC14	10731304286889

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status :	Commercialised
-----------------------	----------------