

## BR550G-CN

APC Back-UPS Pro, 550VA/330W, Tower,  
230V, 6x AS3112 Chinese outlets, AVR, LCD,  
User Replaceable Battery



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	230 V
Rated power in W	330 W
Rated power in VA	550 VA
Output connection type	3 chinese outlet 3 chinese outlet surge
Cable length	1.83 M
Battery type	Lead-acid battery

### Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 H
Number of battery replacement quantity	1
Battery charger power	8 W rated
Battery life	3...5 Year(S)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

### General

Provided equipment	Cat 5 Ethernet cable CD with software User manual USB cable warranty card
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Colour	Black
Height	19 Cm
Width	9.1 Cm
Depth	31 Cm
Net weight	6.53 Kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	Australian/Chinese
Input voltage limits	176...282 V
Maximum input current	6 A
Switching current capacity	7 A

## Output

Maximum configurable power in W	330 W
Output frequency	50 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	550 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CCC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 M
Acoustic level	40 dBA

## Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm





## Surge Protection and Filtering

Surge energy rate	420 J
-------------------	-------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.2 Cm
Package 1 Width	44.2 Cm
Package 1 Length	13.8 Cm
Package 1 Weight	7.71 Kg
SCC14	10731304286896

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	<a href="#"> Yes</a>
Environmental Disclosure	<a href="#"> Product Environmental Profile</a>
Circularity Profile	<a href="#"> End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status :	Commercialised
-----------------------	----------------