

BR900G-RS
APC Back-UPS Pro, 900VA/540W, Tower,
230V, 5x CEE 7/7 Schuko outlets, AVR, LCD,
User Replaceable Battery



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Rated power in W	540 W
Rated power in VA	900 VA
Output connection type	3 Schuko CEE 7 2 Schuko CEE 7 surge
Cable length	1.52 M
Battery type	Lead-acid battery

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 H
Number of battery replacement quantity	1
Battery charger power	20 W rated
Battery life	3...5 Year(S)
Extended runtime	0

General

Provided equipment	CD with software User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Physical

Height	10 Cm
Width	25 Cm
Depth	38.2 Cm
Net weight	10.72 Kg
Mounting support	Desktop
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	156...300 V adjustable 176...294 V
Maximum input current	8 A
Switching current capacity	10 A

Output

Maximum configurable power in W	540 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	900 VA
Transfer time	8 ms typical : 10 ms maximum

Conformance

Product certifications	GOST
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 M
Acoustic level	45 dBA

Communications & Management

Control panel	Multifunction LCD status and control console
---------------	--

Surge Protection and Filtering

Surge energy rate	613 J
Data line protection	RJ11 modem/fax/DSL protection (two wire single line)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	48.7 Cm
Package 1 Width	33.7 Cm
Package 1 Length	22.5 Cm
Package 1 Weight	12.4 Kg
SCC14	10731304295683

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **End of commerc. announced**

BR900G-RS may be replaced by any of the following products:



BR900G-GR

APC Back-UPS Pro, 900VA/540W, Tower, 230V, 5x CEE 7/7 Schuko outlets, AVR, LCD, User Replaceable Battery

Qty 1

Substitution date: |