

BV500I-GR

APC EASY UPS BV 500VA, AVR, Schuko Outlet, 230V



Overview

Model Name	APC EASY UPS BV 500VA, AVR, Schuko Outlet, 230V
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Algeria , Angola , Armenia , Azerbaijan , Bahrain , Belarus , Benin , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cameroon , Central African Republic , Chad , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Croatia , Djibouti , Egypt , Equatorial Guinea , Eritrea , Ethiopia , Gabon , Gambia , Georgia , Ghana , Gibraltar , Greece , Guadeloupe , Guinea , French Guiana , Hungary , Iran (Islamic Republic Of) , Iraq , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Lebanon , Lesotho , Liberia , Madagascar , Malawi , Mali , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Niger , Nigeria , Oman , Pakistan , Poland , Qatar , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Sudan , Suriname , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Togo , Tunisia , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uzbekistan , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity	300 Watts / 500 VA
Max Configurable Power (Watts)	300 Watts / 500 VA
Nominal Output Voltage	230V
Nominal Output Voltage	Line Interactive
Waveform Type	Stepped approximation to a sine wave
Output Connections	(4) Schuko CEE 7 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	Schuko CEE 7/7P
Cord Length	1.52 meters

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
--------------	--

Communications & Management

Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Physical

Maximum Height	93.0 mm
Maximum Width	161.0 mm
Maximum Depth	305.0 mm
Net Weight	3.9 kg
Shipping Weight	4.2 kg
Shipping Height	237.0 mm
Shipping Width	143.0 mm
Shipping Depth	373.0 mm
SCC Codes	1073130433828 1

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 90 %
Operating Elevation	0-1968.3 meters
Audible noise at 1 meter from surface of unit	40.000 dB

Conformance

Approvals	CE
-----------	----