

BV500I

APC EASY UPS BV 500VA, AVR, IEC Outlet, 230V



Overview

Model Name	APC EASY UPS BV 500VA, AVR, IEC Outlet, 230V
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Albania , Algeria , Angola , Azerbaijan , Bahrain , Benin , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cameroon , Central African Republic , Chad , Congo , CONGO , THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Croatia , Cyprus , Czech Republic , Djibouti , Egypt , Equatorial Guinea , Eritrea , Ethiopia , Gabon , Gambia , Georgia , Ghana , Gibraltar , Greece , Guadeloupe , Guinea , French Guiana , Iran (Islamic Republic Of) , Iraq , Israel , Jordan , Kenya , Kuwait , Lebanon , Lesotho , Liberia , Madagascar , Malawi , Mali , Malta , Martinique , Mauritania , Mauritius , Mayotte , Moldova , Republic Of , Mongolia , Morocco , Mozambique , Namibia , Niger , Nigeria , Oman , Pakistan , Poland , Qatar , Reunion , Romania , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Somalia , South Africa , Sudan , Suriname , Tajikistan , TANZANIA , UNITED REPUBLIC OF , Togo , Tunisia , Turkmenistan , Uganda , United Arab Emirates , Uzbekistan , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity	300 Watts / 500 VA
Max Configurable Power (Watts)	300 Watts / 500 VA
Nominal Output Voltage	230V
Nominal Output Voltage	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(6) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1.52 meters

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
--------------	--

Communications & Management

Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Physical

Maximum Height	93.0 mm
Maximum Width	161.0 mm
Maximum Depth	305.0 mm
Net Weight	3.9 kg
Shipping Weight	4.2 kg
Shipping Height	237.0 mm
Shipping Width	143.0 mm
Shipping Depth	373.0 mm
SCC Codes	1073130433826 7

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 90 %
Operating Elevation	0-1968.3 meters
Audible noise at 1 meter from surface of unit	40.000 dB

Conformance

Approvals	CE
-----------	----

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs