

# Product data sheet

Specifications



## SE Easy UPS, 800VA, Floor/Wall Mount, 230V, 4x AS3112 Australian outlets, AVR

BVS800I-AZ

### Overview

|           |                  |
|-----------|------------------|
| Lead Time | Usually in Stock |
|-----------|------------------|

### Main

|                           |  |
|---------------------------|--|
| Product Or Component Type | Uninterruptible power supply (UPS)                           |
| Cable Length              | 1.52 m   |
| Battery Type              | Lead-acid battery<br>Sealed rechargeable<br>Internal battery |
| Range Of Product          | Easy UPS 1Ph BVS Series                                      |

### Complementary

|                       |   |
|-----------------------|---|
| Display Type          | LED indicator   |
| Transfer Time         | 6 ms typical : 10 ms maximum  |
| Power Range           | 800 VA  |
| Electrical Connection | Output: 4 outlet Australian<br>Input: 1 cable   |
| Local Signalling      | Alarm, distinctive for low battery<br>Alarm, continuous or intermittent tone for overload<br>LCD display for status and alert |
| Charging Time         | 8 h   |
| Net Weight            | 5.3 kg  |
| Height                | 9.25 cm   |
| Width                 | 16.05 cm  |
| Depth                 | 30.5 cm   |

### Environment

|                                       |  |
|---------------------------------------|--|
| Relative Humidity                     | 0...90 %, non-condensing   |
| Operating Altitude                    | 0...1968.3 m   |
| Ambient Air Temperature For Operation | 0...40 °C  |
| Standards                             | EN/IEC 62040-1:2019/A11:2021<br>EN/IEC 62040-2:2006/AC:2006<br>EN/IEC 62040-2:2018 |
| Product Certifications                | CE<br>RCM  |

### Physical

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                  |            |
|------------------|------------|
| Mounting Support | Wall-mount |
|------------------|------------|

## Packing Units

|                              |                |
|------------------------------|----------------|
| Unit Type Of Package 1       | PCE            |
| Number Of Units In Package 1 | 1              |
| Package 1 Height             | 2.362 cm       |
| Package 1 Width              | 1.422 cm       |
| Package 1 Length             | 3.734 cm       |
| Package 1 Weight             | 5.602 kg       |
| Scc14                        | 10731304346460 |

## Contractual warranty

|          |         |
|----------|---------|
| Warranty | 2 years |
|----------|---------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

|                          |   |
|--------------------------|---|
| Reach Regulation         | <a href="#">REACH Declaration</a>   |
| Eu Rohs Directive        | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | <a href="#">End of Life Information</a>   |