

# Product data sheet

Specifications



## APC Power-Saving Back-UPS XS 1000VA, 120V

BX1000G-CA

 **Discontinued on:** Jun 14, 2022

 **Discontinued**




### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	120 V
Rated Power In W	600 W
Rated Power In Va	1000 VA
Output Connection Type	4 NEMA 5-15R 4 NEMA 5-15R surge
Cable Length	1.83 m
Number Of Cables	1
Battery Type	Lead-acid battery

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a> 
Efficiency	<a href="#">View Efficiency Graph</a> 
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	16 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	11 W rated
Battery Life	3...5 year(s)
Replacement Battery	<a href="#">APCRBC123</a> 
Extended Runtime	0

### General

Provided Equipment	user manual USB cable
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Physical

Colour	Black
Height	25 cm
Width	10 cm
Depth	38.2 cm
Net Weight	10.72 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	88...139 V
Maximum Input Current	12 A
Switching Current Capacity	15 A

## Output

Maximum Configurable Power In W	600 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Bypass Type	Built-in bypass
Maximum Output Current	15 A
Maximum Configurable Power In Va	1000 VA
Transfer Time	8 ms typical : 12 ms maximum

## Conformance

Product Certifications	DOC/Industry Canada UL listed
Equipment Protection Policy	Lifetime : \$150000

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...9842 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...14999.82 m
Acoustic Level	45 dBA

## Communications & Management

Control Panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge Energy Rate	354 J
Noise Suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Let Through Voltage Rating	300 V

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	33.7 cm
Package 1 Width	22.5 cm
Package 1 Length	48.7 cm
Package 1 Weight	11.675 kg
Scc14	10731304278792

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)