


Product data sheet

Specifications



APC Back-UPS 1100VA, 230V, AVR, 6 chinese outlets

BX1100CI-CN

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Rated power in W	660 W
Rated power in VA	1100 VA
product or component type	Uninterruptible power supply (UPS)
output connection type	6 chinese outlet
Cable length	1.16 m
Battery type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery charger power	19 W rated
Battery life	3...5 year(s)
Replacement battery	APCRBC113
Extended runtime	0

General

Provided equipment	user manual warranty card
product web sub-family	Entry level
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	21.5 cm
Width	13 cm
Depth	33.6 cm
net weight	12 kg
mounting support	Desktop
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
plug standard	Australian/Chinese
Input voltage limits	150...280 V
Maximum input current	5 A
Switching current capacity	10 A

Output

Maximum configurable power in W	660 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Maximum configurable power in VA	1100 VA
Transfer time	8 ms typical : 10 ms maximum

Conformance

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	------------------------------------------------------------------------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...9144.0000000000 m
Acoustic level	45 dBA

Communications & Management

control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.5 cm
Package 1 Width	44 cm
Package 1 Length	24.5 cm
Package 1 Weight	12.92 kg
SCC14	00731304291381

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)