



Commercial status

End-of-Sale Notice : SEP 09, 2021

⚠ End-of-Sale Notice

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V
Rated power in W	780 W
Rated power in VA	1300 VA
Output connection type	5 NEMA 5-15R 5 NEMA 5-15R surge
Cable length	1.83 M
Number of cables	1
Battery type	Lead-acid battery

Batteries & Runtime

Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	16 H
Number of battery replacement quantity	1
Battery charger power	9 W rated
Battery life	3...5 Year(S)
Extended runtime	0

General

Provided equipment	User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	30.1 Cm
Width	11.2 Cm
Depth	38.2 Cm
Net weight	10.5 Kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Output

Maximum configurable power in W	780 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Bypass type	Built-in bypass
Maximum configurable power in VA	1300 VA
Transfer time	8 ms typical : 12 ms maximum

Conformance

Product certifications	California Energy Commission (CEC)[RETURN]TÜV[RETURN]UL listed
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...30000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 M
Acoustic level	45 dBA

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm

Surge Protection and Filtering

Surge energy rate	354 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Let through voltage rating	330 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.7 Cm
Package 1 Width	48.8 Cm
Package 1 Length	23.8 Cm

Package 1 Weight	12.85 Kg
SCC14	10731304268380

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and-lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Product Life Status : **End of commercialisation**