

Product data sheet

Specifications



APC Back-UPS XS 1300VA, LCD, 120V, Retail, Factory Serviced

BX1300LCDW

⚠ Discontinued on: Jul 16, 2021

⚠ Discontinued

Overview

Lead Time While Supplies Last

Main

Main Input Voltage	120 V
Rated Power In W	780 W
Rated Power In Va	1300 VA
Output Connection Type	6 NEMA 5-15R 2 NEMA 5-15R surge
Cable Length	1.83 m
Number Of Cables	1

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Extended Runtime	0

General

Provided Equipment	CD with software user manual USB cable
Max Runtime	60 min
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Charcoal
Height	22.2 cm
Width	13.3 cm
Depth	35.6 cm
Net Weight	13.5 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	60 Hz +/- 3 Hz
Input Voltage Limits	88...139 V
Maximum Input Current	13 A
Switching Current Capacity	15 A

Output

Maximum Configurable Power In W	780 W
Output Frequency	60 Hz sync to mains
Crest Factor	3 : 1
Ups Type	Line interactive
Maximum Output Current	12 A
Maximum Configurable Power In Va	1300 VA

Conformance

Product Certifications	NOM TÜV
Equipment Protection Policy	Lifetime : \$75000

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-5...45 °C
Storage Relative Humidity	0...95 %

Surge Protection and Filtering

Surge Energy Rate	340 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	24.8 cm
Package 1 Length	45.7 cm
Package 1 Weight	14.619 kg

Contractual warranty

Warranty

1 year repair or replace