

# APC BACK-UPS XS 1500VA LCD 120V RETAIL



APC Back-UPS XS, 865 Watts / 1500  
VA, Input 120V / Output 120V

**Includes:** CD with software, USB cable, User Manual

**Standard Lead Time** : Usually in Stock

### Runtime Chart

## BX1500LCD

## Contact Sales

Add Options

 [Email Technical Specifications](#)

 [Printer Friendly](#)

[+ More Images](#)

## Technical Specifications



## Product Overview

## Documentation


## Software & Firmware

## Options

## Output

Output Power Capacity	865 Watts / 1500 VA	
Max Configurable Power	865 Watts / 1500 VA	
Nominal Output Voltage	120V	
Output Frequency (sync to mains)	60 Hz	
Crest Factor	3 : 1	
Waveform Type	Stepped approximation to a sinewave	
Output Connections	(2) NEMA 5-15R (Surge Protection)	
	(6) NEMA 5-15R (Battery Backup)	

## Input

Nominal Input Voltage	120V
Input Frequency	60 Hz +/- 3 Hz
Input Connections	NEMA 5-15P 
Cord Length	1.83 meters
Input voltage range for main operations	88 - 139V
Maximum Input Current	13A
Input Breaker Capacity	15A

## Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	16 hour(s)
Replacement Battery	<a href="#">APCRBC109</a>
RBC™ Quantity	1
Typical Backup Time at Half Load	13.4 minutes (432.5 Watts)
Typical Backup Time at Full Load	3.3 minutes (865 Watts)
Runtime Chart	<a href="#">Back-UPS XS</a>

## Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	340 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Dataline protection	RJ-45 Modem/Fax protection (two wire single line),Co-axial Video / Cable protection

## Physical

Maximum Height	222.00 mm
Maximum Width	133.00 mm
Maximum Depth	356.00 mm
Net Weight	13.50 KG
Shipping Weight	15.10 KG
Shipping Height	305.00 mm
Shipping Width	248.00 mm
Shipping Depth	457.00 mm
Master Carton Units	2.00
Master Carton Weight	31.78 KG
Color	Charcoal
SCC Codes	1073130424792 7
Units per Pallet	24.00

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA

## Conformance

Regulatory Approvals	FCC Part 15 Class B,FCC Part 68,NOM,TUV
Standard Warranty	3 years repair or replace

\*\*The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.