

# Product data sheet

Specifications



## APC Back-UPS 575VA, 120V, AVR, LAM, 6 NEMA outlets (2 surge)

BX575U-LM

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	120 V
Rated power in W	320 W
Rated power in VA	575 VA
product or component type	Uninterruptible power supply (UPS)
output connection type	4 NEMA 5-15R 2 NEMA 5-15R surge
Cable length	1.5 m
Number of cables	1
Battery type	Lead-acid battery

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	6 h
Number of battery replacement quantity	1
Battery charger power	13 W rated
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC110</a>
Extended runtime	0

### General

Provided equipment	user manual
product web sub-family	Entry level
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### Physical

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Colour	Black
Height	27.85 cm
Width	16 cm
Depth	8.85 cm
net weight	5.2 kg
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Network frequency	47...63 Hz
Input voltage limits	78...150 V
Maximum input current	12 A
Switching current capacity	15 A
Input protection type	3-pole circuit breaker

## Output

Maximum configurable power in W	320 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Square wave
Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
Maximum output current	12 A
Maximum configurable power in VA	575 VA
Transfer time	6 ms typical : 10 ms maximum

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Acoustic level	45 dBA

## Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.9 cm
Package 1 Width	12.8 cm
Package 1 Length	21.5 cm
Package 1 Weight	5.4 kg
SCC14	10731304310096

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Weee   The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile   [End of Life Information](#)