

# Product data sheet

Specifications



## APC Back-UPS 625VA, 230V, AVR, floor, 3 universal outlets

BX625CI-MS

### Overview

Lead Time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	230 V
Rated Power In W	325 W
Rated Power In Va	625 VA
Nb Of Power Socket Outlets	3 universal receptacle
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Number Of Battery Filled Slots	1
Number Of Battery Free Slots	0
Battery Recharge Time	6 h
Battery Charger Power	11 W rated
Battery Power In Vah	65 VAh runtime
Battery Life	2...4 year(s)
Replacement Battery	<a href="#">APCRBC110</a>
Extended Runtime	0

### General

Provided Equipment	1, detachable 2.0 m NEMA 5-15P to IEC C13 power cord user manual
Product Web Sub-Family	Entry level
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

### Physical

Colour	Black
--------	-------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	27.85 cm
Width	16 cm
Depth	8.85 cm
Net Weight	5 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	45...65 Hz
Input Voltage Limits	151...299 V
Maximum Input Current	3 A
Switching Current Capacity	7 A
Input Protection Type	3-pole circuit breaker

## Output

Maximum Configurable Power In W	325 W
Output Frequency	50/60 Hz +/- 1 Hz unsynchronised
Ups Type	Line interactive
Waveform Type	Square wave
Efficiency	65.3 % (full load) 75.8 % (half load)
Maximum Configurable Power In Va	625 VA
Transfer Time	4 ms typical : 8 ms maximum

## Conformance

Equipment Protection Policy	No EPP for ASEAN
-----------------------------	------------------

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	0...95 %
Acoustic Level	45 dBA

## Surge Protection and Filtering

Surge Energy Rate	273 J
-------------------	-------

## Packing Units

Package 1 Height	39.9 cm
Package 1 Width	21.5 cm

Package 1 Length	12.8 cm
Package 1 Weight	5.2 kg
Number Of Units In Package 2	1
Number Of Units In Package 3	100
Scc14	10731304308178

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™** label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products. **Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient   Take-back

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant  
[EU RoHS Declaration](#)