

Back-UPS XS  
APC BACK-UPS XS 800VA 120V CANADA



APC Back-UPS XS, 540 Watts / 800 VA, Input 120V / Output 120V , Interface Port USB

**Includes:** CD with software, Cord management straps, Free trial of anti-virus : firewall : email privacy : system recovery and online backup software, USB cable, User Manual

★★★★★  
Be the first to [write a review](#)

BX800-CN  
DISCONTINUED

Email Technical Specifications  
Printer Friendly



Product Category

- Computer and Peripheral
  - > Back-UPS
  - > Back-UPS ES
  - > Back-UPS Pro
  - > APC ES
  - > APC RS
- Home UPS (2)
- Network and Server (3)
- Data Center and Facility 3 Phase (14)
- UPS Management (7)


Return to Uninterruptible Power Supply (UPS)

Technical SpecificationsProduct OverviewDocumentationSoftware & FirmwareOptionsRatings and Reviews

Output

Output Power Capacity	540 Watts / 800 VA	
Max Configurable Power	540 Watts / 800 VA	
Nominal Output Voltage	120V	
Output Connections	(3) NEMA 5-15R (Surge Protection)	
	(4) NEMA 5-15R (Battery Backup)	

Input

Nominal Input Voltage	120V	
Input Frequency	47 - 63 Hz	
Input Connections	NEMA 5-15P	
Cord Length	1.83 meters	
Input voltage range for main operations	88 - 139V	
Input voltage adjustable range for mains operation	78 - 152V	

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1
Typical recharge time	8 hour(s)
Replacement Battery	<a href="#">RBC32</a>
RBC™ Quantity	1
Runtime Graph	



Hover over the line on the graph above to view the runtime at any desired load

Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.

[View Enlarged Graph](#)[View Runtime Chart](#)

Communications & Management

Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating	320 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line)

Physical

Maximum Height	229.00 mm
Maximum Width	102.00 mm
Maximum Depth	324.00 mm
Net Weight	9.32 KG
Shipping Weight	10.24 KG
Shipping Height	305.00 mm
Shipping Width	229.00 mm
Shipping Depth	432.00 mm
Master Carton Units	2.00
Color	Charcoal
SCC Codes	1073130421293 2
Units per Pallet	32.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA
Online Thermal Dissipation	170.00 BTU/hr

Conformance

Regulatory Approvals	CSA,FCC Part 15 Class B,FCC Part 68,UL 1449,UL 1778,UL Listed
Standard Warranty	2 years repair or replace

\*\*The time to recharge to 80% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.