Product data sheet Characteristics

BX800CI-ZA APC Back-UPS 800VA, 230V, AVR, South Africa



Overview Model Name APC Back-UPS 800VA, 230V, AVR, South Africa Includes Telephone Cable , User Manual , Warranty card Standard Lead Time Usually in Stock Product Distribution Botswana , Lesotho , Mozambique , Namibia , South Africa

Output

Output Power Capacity	480 Watts / 800 VA	
Max Configurable Power (Watts)	480 Watts / 800 VA	
Nominal Output Voltage	230V	
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz	
	Line Interactive	
Output Connections	(4) BS 546 (Battery Backup)	

Input

The second secon		
Nominal Input Voltage	230V	
Input Connections	BS 546	
Cord Length	1.16 meters	
Input voltage range for main operations	150 - 280 V	
Maximum Input Current	7 A	
Input Breaker Capacity	7 A	

Batteries & amp; Runtime

Replacement Battery RBC17	Replacement battery	RBC17	
---------------------------	---------------------	-------	--

Communications & Danagement

Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuoustone alarm

Surge Protection and Filtering

Surge energy rating	273 Joules
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line)

Physical

y		
Maximum Height	215.0 mm	
Maximum Width	130.0 mm	
Maximum Depth	336.0 mm	
Net Weight	8.0 kg	
Shipping Weight	8.94 kg	
Shipping Height	295.0 mm	
Shipping Width	245.0 mm	
Shipping Depth	440.0 mm	
SCC Codes	0073130429148 0	
Units per Pallet	24.0	

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 40 °C
Storage Elevation	0-9000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals CE , EN/IEC 60950-1 , NEMKO , SABS
--

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs

