Product Category

Return to Broadband

Power Systems











> You are here: Home > Products > PowerShield

PowerShield

PowerShield 24W 12VDC NA3 B F

Complete line of reliable and flexible customer premise powering solutions for broadband telecommunication applications.

Your Business

Support

Includes: User Manual

Be the first to write a review

Standard Warranty

CP24B12NA3-F DISCONTINUED



Printer Friendly

Company

Output	
Output Voltages	12
Output Power Capacity	27 Watts / 27 VA
Max Configurable Power	27 Watts / 27 VA
Input	
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC 320 C5
Cord Length	2.44 meters
Input voltage range for main operations	87 - 264V
Input ∀oltages	100 - 240
Number of Power Cords	1
Physical	
Maximum Height	295.00 mm
Maximum Width	282.00 mm
Maximum Depth	94.00 mm
Net Weight	8.18 KG
Shipping Weight	8.42 KG
Shipping Height	417.00 mm
Shipping Width	417.00 mm
Shipping Depth	218.00 mm
Color	Beige
Units per Pallet	28.00
Environmental	
Operating Environment	-20 - 45 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 45 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters
Conformance	
Regulatory Approvals	cUL Listed,C-tick,CSA 22.2 No. 950,EN 55022 Class B,EN 60950,FCC Part 15 Class B,UL 1950,UL Listed

2 years repair or replace