

> You are here: Home > Products > PowerShield

PowerShield

PowerShield 24W 12VDC NA3 F Desktop

Complete line of reliable and flexible customer premise powering solutions for broadband telecommunication applications.

**Includes:** User Manual

★★★★★

Be the first to [write a review](#)

CP24D12NA3-F

DISCONTINUED

Email Technical Specifications

Printer Friendly

< Return to Broadband Power Systems

Technical Specifications

Documentation

Options

Ratings and Reviews

Output

Output Voltages	12
Output Power Capacity	27 Watts / 27 VA
Max Configurable Power	27 Watts / 27 VA

Input

Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC 320 C5
Cord Length	2.44 meters
Input voltage range for main operations	87 - 264V
Input Voltages	100 - 240
Number of Power Cords	1

Physical

Maximum Height	241.00 mm
Maximum Width	241.00 mm
Maximum Depth	70.00 mm
Net Weight	3.64 KG
Shipping Weight	4.27 KG
Shipping Height	323.00 mm
Shipping Width	325.00 mm
Shipping Depth	191.00 mm
Color	Blue

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	C-tick,CSA 22.2 No. 950,EN 55022 Class B,EN 60950,FCC Part 15 Class B,UL 1950,UL Listed,VDE
Standard Warranty	2 years repair or replace