

PowerShield

PowerShield 24W 12VDC NA3 U F2

CP24U12NA3-F2

DISCONTINUED

- Email Technical Specifications
- Printer Friendly

Product Category

Complete line of reliable and flexible customer premise powering solutions for broadband telecommunication applications.

Includes: User Manual



Be the first to [write a review](#)



[More Images](#)

Technical Specifications

Options

Ratings and Reviews

Output

Output Power Capacity	24 Watts / 24 VA
Max Configurable Power	24 Watts / 24 VA

Input

Input Frequency	47 - 70 Hz (auto sensing)
Input Connections	IEC 320 C5
Cord Length	2.44 meters
Input voltage range for main operations	87 - 264V
Input Voltages	100 - 240
Number of Power Cords	1

Communications & Management

Control panel	LED Status display with On Line : On Battery,Output power on indicator LED
---------------	--

Physical

Maximum Height	191.00 mm
Maximum Width	241.00 mm
Maximum Depth	76.00 mm
Net Weight	3.42 KG
Shipping Weight	4.10 KG
Shipping Height	343.00 mm
Shipping Width	343.00 mm
Shipping Depth	114.00 mm
Color	Beige
Units per Pallet	90.00

Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	cUL Listed,C-tick,CE,EN 55022 Class B,EN 55024,EN 60950,EN 61000-3-2,FCC Part 15 Class B,UL 60950,VDE
Standard Warranty	2 years repair or replace