

Product Category

< Return to Broadband Power Systems

PowerShield

PowerShield 24W 12VDC NA3 U F5



Complete line of reliable and flexible customer premise powering solutions for broadband telecommunication applications.

Includes: User Manual

★★★★★
Be the first to [write a review](#)

CP24U12NA3-F5

DISCONTINUED

 Email Technical Specifications

 Printer Friendly

+ [More Images](#)

Technical Specifications

Documentation

Options

Ratings and Reviews

Output	
Output Power Capacity	27 Watts / 24 VA
Max Configurable Power	24 Watts / 24 VA
Input	
Input Frequency	47 - 70 Hz (auto sensing)
Input Connections	IEC 320 C5
Cord Length	2.44 meters
Input voltage range for main operations	87 - 264V
Input Voltages	100 - 240
Number of Power Cords	1
Communications & Management	
Control panel	LED Status display with On Line : On Battery,Output power on indicator LED
Physical	
Maximum Height	191.00 mm
Maximum Width	241.00 mm
Maximum Depth	76.00 mm
Net Weight	3.41 KG
Shipping Weight	4.09 KG
Shipping Height	343.00 mm
Shipping Width	343.00 mm
Shipping Depth	114.00 mm
Color	Beige
Units per Pallet	90.00
Environmental	
Operating Environment	-5 - 45 °C
Operating Relative Humidity	0 - 95%

Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Conformance	
Regulatory Approvals	cUL Listed,C-tick,CE,EN 55022 Class B,EN 55024,EN 60950,EN 61000-3-2,FCC Part 15 Class B,UL 60950,VDE
Standard Warranty	2 years repair or replace