

PowerShield

PowerShield 27W 12VDC NA2 U F



More Images

Complete line of reliable and flexible customer premise powering solutions for broadband telecommunication applications.

Includes: User Manual



Be the first to write a review

CP27U13NA2

DISCONTINUED

Email Technical Specifications

Printer Friendly

Locate a Partner

Product Category

Return to Broadband Power Systems

Technical Specifications

Product Overview

Documentation

Options

Ratings and Reviews

Output

Output Voltages	12
Output Power Capacity	27 Watts / 0 VA
Max Configurable Power	27 Watts / 0 VA

Input

Input Frequency	47 - 70 Hz (auto sensing)
Input Connections	IEC 320 C5
Cord Length	2.44 meters
Input voltage range for main operations	87 - 264V
Input Voltages	100 - 240
Number of Power Cords	1

Communications & Management

Control panel	LED Status display with On Line : On Battery, Output power on indicator LED
---------------	---

Physical

Maximum Height	191.00 mm
Maximum Width	241.00 mm
Maximum Depth	76.00 mm
Net Weight	3.42 KG
Shipping Weight	4.10 KG
Shipping Height	343.00 mm
Shipping Width	343.00 mm
Shipping Depth	114.00 mm
Color	Beige
Units per Pallet	90.00

Environmental

Operating Environment	-20 - 50 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	cUL Listed, C-tick, CE, EN 55022 Class B, EN 60950, EN 61000-3-2, FCC Part 15 Class B, IEC 60950, UL 60950, UL Listed
Standard Warranty	2 years repair or replace

Sustainable Offer Status