

Product data sheet

Specifications



Magnum VS 100 W/SNMP -- GMT Distribution

DCM00K06SGMT

⚠ Discontinued on: Jun 10, 2022

⚠ Discontinued

Overview

Lead time Usually Ships within 4 Weeks

Main

Main Input Voltage	100 V 120 V 200 V 208 V 230 V
Rated power in W	500 W
Rated power in VA	10 VA
Number of rack unit	6U
Battery type	External battery system
Provided equipment	Rack mounting brackets User manual

Physical

Colour	Black
Height	26.7 cm
Width	43.8 cm
Depth	33 cm
net weight	18 kg
mounting mode	Rack-mounted

Input

Network frequency	47...63 Hz
Number of input connectors	1 hard wire 3-wire
Input Power Factor at Full Load	0.99
Maximum input current	5.5 A
Overcurrent protection	Integral fuse in each rectifier
Input voltage limits	88...264 V

Output

Maximum configurable power in W 5000 W

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Grounding polarity	Positive ground
Grounding option	Positive ground
Low voltage disconnect	Battery circuit
Low voltage disconnect option	Battery circuit None
Number of factory setting voltage	54 V

Conformance

Product certifications	CE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A UL 1950

Communications & Management

control panel	LED status display of rectifier healthy Network link status LED
Visible alarm	Current limit Distribution failure Input OK Major alarm Minor alarm Output OK Overvoltage User defined
Form C relay alarm	Major alarm Minor alarm User defined

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.7 cm
Package 1 Width	55.9 cm
Package 1 Length	47 cm
Package 1 Weight	22.952 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------