

Product data sheet

Specifications



DELL Smart-UPS 1440VA, 120V, rackmount, 2U, 6x NEMA 5-15R outlets

DLA1500RM2U

⚠ Discontinued on: 15 October 2021

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	980 W
Rated power in VA	1440 VA
Input Connection Type	IEC 60320 C14 NEMA 5-15P
Output connection type	6 NEMA 5-15R
Number of rack unit	2U
Cable length	2.44 m
Number of cables	2
Battery type	Lead-acid battery
Provided equipment	CD with software Rack mounting support rails Smart UPS signalling RS-232 cable User manual USB cable

Physical

Colour	Black
Height	8.9 cm
Width	48.3 cm
Depth	45.7 cm
Net weight	28.64 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	75...154 V adjustable 82...144 V

Output

Maximum configurable power in W	980 W
UPS type	Line interactive


Conformance

Product certifications	CSA
Standards	FCC part 15 class A UL 1778
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	46 dBA
Heat dissipation	171 Btu/h

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Replacement battery	RBC24 

Communications & Management

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Optional
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators

Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Recommended replacement(s)

DLA1500RM2U is replaced by the following group of products:

1x		APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD SMT1500RM2UC
----	---	---