

Product data sheet

Specifications



DELL Smart-UPS 1500VA, 230V, rackmount, 2U, 4x IEC 60320 C13 & 2x IEC Jumpers outlets

DLA1500RMI2U

⚠ Discontinued on: 04 January 2022

⚠ End-of-service on: 16 January 2022

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Rated power in W	980 W
Rated power in VA	1500 VA
Nb of power socket outlets	4 IEC 60320 C13 2 IEC Jumpers
Main Output Voltage	230 V
Main Input Voltage	230 V
Plug standard	IEC 60320 C14
Number of rack unit	2U
Number of cables	1

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Provided equipment	CD with software Rack mounting support rails Smart UPS signalling RS-232 cable User manual USB cable

Physical

Mounting location	Front
Mounting mode	Rack-mounted
Mounting preference	No preference
Depth	45.7 cm
Height	8.9 cm
Net weight	28.64 kg

Width	48.3 cm
Two post mountable	0
USB compatible	No
Colour	Black

Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Maximum configurable power in VA	1500 VA
Maximum configurable power in W	980 W
Transfer time	2 ms typical
UPS type	Line interactive

Conformance

Product certifications	C-Tick CE IRAM TÜV VDE
Standards	EN 50091-1 EN 50091-2

Environmental

Acoustic level	46 dBA
Heat dissipation	171 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery type	Lead-acid battery
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	4...6 year(s)
Battery power in VAH	432 VAh runtime

Battery charger power	144 W rated
-----------------------	-------------

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Emergency power off	Optional
Free slots	1

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	31.91 kg
Package 1 Height	25.4 cm
Package 1 width	59.4 cm
Package 1 Length	60.3 cm
Number of Units in Package 2	1
Number of Units in Package 3	16

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Recommended replacement(s)