

Product data sheet

Specifications

Dell Smart-UPS 2200VA USB RM 2U 120V



DLA2200RM2U

 **Discontinued on:** Jun 14, 2022

 **Discontinued**


Overview

Lead Time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated Power In W	1980 W
Rated Power In Va	2200 VA
Input Connection Type	IEC 60320 C20 NEMA 5-20P
Output Connection Type	2 NEMA 5-15R 2 NEMA 5-20R 1 NEMA L5-20R
Number Of Rack Unit	2U
Cable Length	2.44 m
Number Of Cables	2
Battery Type	Lead-acid battery
Provided Equipment	CD with software Country-specific detachable power cord Smart UPS signalling RS-232 cable User manual USB cable

Batteries & Runtime

Run Time	View Runtime Graph 
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	3 h
Number Of Battery Replacement Quantity	1
Battery Life	3...5 year(s)
Battery Charger Power	163 W rated

General

Number Of Power Module Filled Slots 0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Free Slots	0
Redundant	No

Physical

Colour	Black
Height	8.9 cm
Width	48.3 cm
Depth	66 cm
Net Weight	43.64 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Usb Compatible	No

Input

Input Voltage Limits	75...154 V adjustable 82...144 V
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Maximum Configurable Power In Va	2200 VA
Maximum Configurable Power In W	1980 W
Transfer Time	2 ms typical
Ups Type	Line interactive

Conformance

Product Certifications	BSMI CSA
Equipment Protection Policy	Lifetime : \$150000

Environmental

Acoustic Level	47 dBA
Heat Dissipation	300 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control Panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
---------------	--

Emergency Power Off	Yes
Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge Energy Rate	480 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	25.4 cm
Package 1 Width	62.2 cm
Package 1 Length	98 cm
Package 1 Weight	56.701 kg

Contractual warranty

Warranty	3 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)