


# Product data sheet

Specifications



## Parallel Maintenance Bypass Panel, 10-200kVA 400V wallmount, for Easy UPS 3S/3M

E3MBPAR60K200H

### Overview

Presentation	Maintenance bypass panel for complete isolation of an Easy UPS 3M in parallel during service operations. Up to three UPSs can be isolated.
Lead Time	Usually Ships within 6 Weeks

### Physical

Colour	White
Height	100 cm
Width	70 cm
Depth	32 cm
Net Weight	62 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

### Environmental

Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-25...55 °C
Storage Relative Humidity	0...95 % non-condensing

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	120 cm
Package 1 Width	57 cm
Package 1 Length	80 cm
Package 1 Weight	92 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Sustainability




**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	<a href="#">Yes</a>
Reach Regulation		<a href="#">REACH Declaration</a>
Eu Rohs Directive		Compliant with Exemptions
China Rohs Regulation		<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information