

Product data sheet

Specifications



Easy UPS 3M 80kVA 400V 3:3 UPS for internal batteries, Start-up 5x8

E3MUPS80KHBS

Overview

| | |
|--------------|--|
| Presentation | Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 80 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. This UPS is for internal batteries, but is supplied without batteries, so you can easily customize the battery runtime. For battery runtime details, see the runtime charts published under the Documents tab. Includes 5x8 start-up service. |
| Lead Time | Usually Ships within 6 Weeks |

Main

| | |
|----------------------|---|
| Main Input Voltage | 400 V 3 phases |
| Other Input Voltage | 380 V 415 V |
| Main Output Voltage | 400 V 3 phases |
| Other Output Voltage | 380 V 415 V |
| Rated Power In W | 80 kW |
| Rated Power In Va | 80 kVA |
| Provided Equipment | Dust filter Installation guide Start-up service |

Batteries & Runtime

| | |
|--------------------------------|-------|
| Battery Type | VRLA |
| Battery Voltage | 240 V |
| Number Of Battery Filled Slots | 0 |
| Number Of Battery Free Slots | 0 |
| Max Current Discharge | 222 A |

Physical

| | |
|----------------|------------------|
| Colour | White (RAL 9003) |
| Height | 197 cm |
| Width | 60 cm |
| Depth | 100 cm |
| Net Weight | 339 kg |
| Usb Compatible | Yes |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Input

| | |
|----------------------------------|---|
| Maximum Input Current | 104 A |
| Max Short Time Withstand Current | 10 kA |
| Input Harmonic Distortion | Less than 3 % for full load |
| Load Power Factor | 0.5 leading to 0.5 lagging without derating |
| Input Power Factor At Full Load | 0.99 |
| Input Voltage Limits | 342...477 V |
| Number Of Input Connectors | 1 hard wire 5-wire (3P + N + E) |
| Network Frequency | 40...70 Hz |

Output

| | |
|----------------------------------|--|
| Maximum Configurable Power In Va | 80 kVA |
| Maximum Configurable Power In W | 80 kW |
| Output Frequency | 50 Hz sync to mains 60 Hz sync to mains |
| Harmonic Distortion | Less than 3 % |
| Output Harmonic Distortion | < 3% linear load and < 5% non-linear load |
| Output Overload Operation | 10 minutes at 125% and 60 seconds at 150% |
| Ups Type | Double conversion online |
| Wave Type | Sine wave |
| Bypass Type | Built-in static bypass |

Conformance

| | |
|------------------------|--|
| Product Certifications | CE EAC RCM |
| Standards | IEC 62040-1-1 IEC 62040-2 IEC 62040-3 ISTA 2B |

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient Air Temperature For Operation | 0...40 °C |
| Relative Humidity | 0...95 % non-condensing |
| Operating Altitude | 0...1500 ft |
| Ambient Air Temperature For Storage | -15...40 °C |
| Storage Relative Humidity | Non-condensing 0...95 % |
| Storage Altitude | 0.00...4572.00 m |
| Acoustic Level | 65 dBA |
| Heat Dissipation | 14850 Btu/h |
| Ip Degree Of Protection | IP20 |

Communications & Management

| | |
|-------|--|
| Alarm | Audible and visible alarms prioritized by severity |
|-------|--|

| | |
|---------------|---------------------------------|
| Control Panel | Touch screen LCD user interface |
|---------------|---------------------------------|

Packing Units

| | |
|------------------|----------|
| Package 1 Height | 210.2 cm |
| Package 1 Width | 75 cm |
| Package 1 Length | 112.5 cm |
| Package 1 Weight | 387 kg |

Contractual warranty

| | |
|----------|---|
| Warranty | 1 year on-site repair or replace with factory authorized Start-Up |
|----------|---|

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

| | |
|--------------------------|---|
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |