


Product datasheet

Specifications



Easy UPS 3S Cold Start Kit

E3SOPT004

Overview

Presentation	Cold start kit that enables the Easy UPS 3S UPS to start up on battery power. The kit includes a cold start board, button, and cables.
Lead time	Usually Ships within 6 Weeks

Main

product or component type	Kit
---------------------------	-----

Physical

Height	2.4 cm
Width	2.1 cm
Depth	6.3 cm
net weight	0.1 kg
mounting mode	Not rack-mountable

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.000000000...15240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.4 cm
Package 1 Width	6.3 cm
Package 1 Length	2.1 cm
Package 1 Weight	0.1 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Rohs Exemption Information	Yes
<hr/>	
Reach Regulation	REACH Declaration
<hr/>	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
<hr/>	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
<hr/>	