



❗ Discontinued

## Main

|                           |                                         |
|---------------------------|-----------------------------------------|
| Range of product          | Powex                                   |
| Product or component type | Service box                             |
| Device presentation       | Pre-wired, with outlets, cable and plug |
| Colour tint               | White                                   |

## Complementary

|                                |                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------|
| Number of gangs                | 5 gangs                                                                              |
| Number of power socket outlets | 5 x 2P + E with shutters, United Kingdom                                             |
| Integrated connection type     | USB port, output voltage= 5 V DC at 1 A<br>USB port, output voltage= 5 V DC at 2.1 A |
| Control type                   | Switch for socket-outlet with LED                                                    |
| Type of cable                  | A05 VVF 2 m 1.25 mm <sup>2</sup>                                                     |
| [Ue] rated operational voltage | 250 V AC at 13 A                                                                     |
| Protection type                | Output surge protection<br>Overload protection                                       |
| Energy peak                    | 1650 J                                                                               |
| Surge current                  | 30000 A                                                                              |
| Surge withstand                | 1200 V                                                                               |
| Response time                  | < 1 ns                                                                               |
| Local signalling               | LED (green) for surge arrester indication<br>LED (red) for insulation fault          |
| Material                       | Phosphor bronze: connections<br>PC: housing<br>Galvanised steel: screw               |
| Surface finish                 | Silkscreened                                                                         |

## Environment

|           |           |
|-----------|-----------|
| Standards | IEC 61058 |
|-----------|-----------|

BS 1363-2  
EN 61643-11  
IEC 60884-2-5  
EN 60950-1  
IEC 60884-1

|                                       |                          |
|---------------------------------------|--------------------------|
| Ambient air temperature for operation | 0...45 °C                |
| Ambient air temperature for storage   | 0...60 °C                |
| Relative humidity                     | 10...95 % non-condensing |

## Packing Units

|                  |            |
|------------------|------------|
| Package 1 Weight | 0.800 g    |
| Package 1 Height | 53.000 mm  |
| Package 1 width  | 180.000 mm |
| Package 1 Length | 573.000 mm |

## Offer Sustainability

|                            |                                                                                                             |
|----------------------------|-------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                           |
| REACH free of SVHC         | Yes                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                            |
| Toxic heavy metal free     | Yes                                                                                                         |
| Mercury free               | Yes                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                     |