

# Product datasheet

Specifications



## Galaxy PWi 10kVA 3:1 Integrated Parallel UPS 220 6 Pulse 220VDC with Input transformer, Start-up 5X8

G1W10MU6PUTS

⚠ Discontinued on: 31 May 2021

⚠ End-of-service on: 18 Oct 2023

⚠ Discontinued

### Overview

Presentation	A versatile 3:1-phase UPS for facility, industrial and data center applications. Configurable system with a comprehensive range of accessories to meet your application demands.
Lead Time	Usually Ships within 2 Weeks

### Main

Main Input Voltage	380 V 3 phases
Other Input Voltage	400 V
Main Output Voltage	220 V
Other Output Voltage	230 V
Rated Power In W	8000 W
Rated Power In Va	10000 VA
Output Connector Type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Battery Type	External battery system
Provided Equipment	Installation guide User manual

### Batteries & Runtime

Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Additional Information	Configurable for 220 or 230V nominal output voltage
Battery Power In Vah	0 VAh runtime
Extended Runtime	0

### General

Product Web Sub-Family	PWi
Bypass Voltage Tolerance	+/- 25 %
Max Bypass Input Current	45 A
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Physical

Height	180 cm
Width	80 cm
Depth	80 cm
Net Weight	305 kg
Mounting Preference	No preference
Usb Compatible	No

## Input

Network Frequency	45...55 Hz
Number Of Input Connectors	1 hard wire 4-wire (3P + E) 1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	323...460 V 380 V
Maximum Input Current	22 A
Switching Current Capacity	32 A
Max Short Time Withstand Current	36 kA
Input Harmonic Distortion	Less than 30 % for full load
Input Protection Type	Circuit breaker
Load Power Factor	0.8
Input Power Factor At Full Load	0.75

## Output

Maximum Configurable Power In W	8000 W
Harmonic Distortion	Less than 5 %
Output Frequency	50 Hz sync to mains 50 Hz +/- 0.1 % unsynchronised
Crest Factor	3 : 1
Wave Type	Sine wave
Output Voltage Tolerance	+/- 1% static
Output Harmonic Distortion	< 3% linear load and < 5% non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Required Output Current Protection	112.5 A
Neutral Output Current	45 A
Bypass Type	Built-in maintenance bypass Built-in static bypass
Efficiency	90 % (full load) 82 % (half load)
Maximum Output Current	112.5 A
Maximum Configurable Power In Va	10000 VA

## Conformance

Standards	EN/IEC 62040-1 IEC 61000-4-5 IEC 62040-2
-----------	--

## Environmental

Ambient Air Temperature For Operation	0...35 °C
Relative Humidity	0...95 %
Operating Altitude	0...3300 ft
Ambient Air Temperature For Storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...10058.40 m
Acoustic Level	60 dBA
Ip Degree Of Protection	IP20

## Communications & Management

Free Slots	1
Control Panel	Multifunction LCD status and control console
Emergency Power Off	Yes

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	202.5 cm
Package 1 Width	93 cm
Package 1 Length	93 cm
Package 1 Weight	365 kg

## Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Under investigation

---