

Product data sheet

Specifications



MGE Galaxy 3500 10kVA 208V with 2 Battery Modules, Start-up 5X8

G35T10KF2B2S

⚠ Discontinued on: Jul 5, 2021

⚠ End-of-service on: Oct 18, 2023

⚠ Discontinued

Overview

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage	208 V 3 phases
Main Output Voltage	208 V 3 phases
Rated power in W	8000 W
Rated power in VA	10000 VA
Output connector type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Connections - terminals	1 screw terminals
Battery type	Lead-acid battery
Provided equipment	Battery modules ship installed Bolt down brackets CD with software Installation guide Network management card Power modules ship installed Smart UPS signalling RS-232 cable Start-up service User manual

Batteries & Runtime

Efficiency	View Efficiency Graph
Number of battery filled slots	2
Number of battery free slots	0
Battery recharge time	5 h
Additional information	Configurable for 200 : 208 or 220V 3 Phase nominal output voltage
Battery charger power	983 W rated
Battery power in VAh	4927 VAh runtime
Battery life	3...5 year(s)
Battery graph comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.8 output.
Extended runtime	0

General

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Height	149.1 cm
Width	35.6 cm
Depth	83.8 cm
net weight	396.82 kg
Mounting preference	No preference
USB compatible	No

Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Input voltage limits	160...240 V
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	0.98

Output

Maximum configurable power in W	8000 W
Harmonic distortion	Less than 3 %
Output frequency	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest factor	Unlimited
Wave type	Sine wave
Output harmonic distortion	< 2% linear load and < 4% non-linear load
Bypass type	Built-in maintenance bypass Built-in static bypass
Maximum configurable power in VA	10000 VA

Conformance

Product certifications	cUL listed CSA UL 1778
Standards	CSA C22.2 No 107.1 ISO 14001 ISO 9001

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...45 °C

Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	51.3 dBA
heat dissipation	1938 Btu/h
NEMA degree of protection	NEMA 12
IP degree of protection	IP51

Communications & Management

Preinstalled device	Network management card 2 with environmental monitoring
---------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	164.3 cm
Package 1 Width	106.2 cm
Package 1 Length	65 cm
Package 1 Weight	427.74 kg

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free

Eu Rohs Directive

Not applicable, out of EU RoHS legal scope

California Proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov