

Product data sheet

Specifications



MGE Galaxy 3500 15kVA 400V 3:1, Start-up 5X8

G35T15K3IS

⚠ Discontinued on: Jul 5, 2021

⚠ To be end-of-service on: Dec 31, 2030

⚠ Discontinued - Service only

Overview

Presentation	UPS is supplied without batteries. To be used with either external third party battery system, or with internal long life modular batteries (SYBTH4).
Lead Time	Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	12000 W
Rated Power In Va	15000 VA
Output Connector Type	Hard wire 3-wire (H N + E) 1
Connections - Terminals	1 screw terminals
Battery Type	External third-party batteries (not supplied)
Provided Equipment	Bolt down brackets Network management card Power modules ship installed Service manual Start-up service User manual

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
Battery Voltage	+/- 192 V (split battery referenced to neutral)
Battery Overload Operation	10 minutes at 125% and 60 seconds at 150%
Battery Power In Vah	0 VAh runtime
Battery Option	SYBTH4 1 2765 VAh SYBTH4 2 5530 VAh SYBTH4 3 8295 VAh SYBTH4 4 11060 VAh

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Graph Comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.8 output.
Extended Runtime	0

General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Height	149.1 cm
Width	52.3 cm
Depth	83.8 cm
Net Weight	261 kg
Mounting Preference	No preference
Usb Compatible	No

Input

Network Frequency	40...70 Hz auto-sensing
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	340...460 V adjustable 400 V 340...460 V 400 V
Maximum Input Current	20 A
Switching Current Capacity	25 A
Input Harmonic Distortion	Less than 5 % for full load
Input Protection Type	3-pole circuit breaker
Inrush Current	200 A peak
Load Power Factor	0.5 leading to 0.5 lagging
Input Power Factor At Full Load	0.98

Output

Maximum Configurable Power In W	12000 W
Harmonic Distortion	Less than 5 %
Output Frequency	47...53 Hz for 50 Hz nominal sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest Factor	Unlimited
Wave Type	Sine wave
Output Voltage Tolerance	+/- 1% static and +/- 5% at 100% load step
Output Harmonic Distortion	< 2% for 0 to 100% linear load and < 5% for full non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Required Output Current Protection	75 A
Bypass Type	Built-in maintenance bypass Built-in static bypass

Maximum Configurable Power In Va	15000 VA
----------------------------------	----------

Conformance

Product Certifications	CE
Standards	EN 50091-2 EN/IEC 62040-3 IEC 61000-3-2 IEC 61000-3-3 ISO 14001 ISO 9001 VFI-SS-111

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...3333 ft
Ambient Air Temperature For Storage	0...40 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	51.3 dBA
Heat Dissipation	1842 Btu/h
Ip Degree Of Protection	IP51

Communications & Management

Free Slots	0
Preinstalled Device	Network management card 2 with environmental monitoring
Control Panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off	Yes

Packing Units

Package 1 Height	164.3 cm
Package 1 Width	65 cm
Package 1 Length	106.2 cm
Package 1 Weight	290 kg

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)
