

# Product data sheet

Specifications



## MGE Galaxy 3500 30kVA 208V with 4 Battery Modules, Start-up 5X8

G35T30KF4B4S

⚠ Discontinued on: Jul 5, 2021

⚠ End-of-service on: Oct 18, 2023

⚠ Discontinued

### Overview

Lead time Usually Ships within 2 Weeks

### Main

Main Input Voltage	208 V 3 phases
Main Output Voltage	208 V 3 phases
Rated power in W	24000 W
Rated power in VA	30000 VA
Output connector type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Connections - terminals	1 screw terminals
Battery type	Lead-acid battery
Provided equipment	Battery modules ship installed Bolt down brackets CD with software Installation guide Network management card Power modules ship installed Smart UPS signalling RS-232 cable Start-up service User manual

### Batteries & Runtime

Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	4
Number of battery free slots	0
Battery recharge time	5 h
Number of battery replacement quantity	4
Additional information	Configurable for 200 : 208 or 220V 3 Phase nominal output voltage
Battery voltage	+/- 192 V (split battery referenced to neutral)
Discharge battery voltage	+/- 154 V
Battery charger power	1965 W rated
Battery power in VAh	9843 VAh runtime
Battery life	3...5 year(s)
Battery graph comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.8 output.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Extended runtime	0
------------------	---

## General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Height	149.1 cm
Width	52.3 cm
Depth	83.8 cm
net weight	629.1 kg
Mounting preference	No preference
USB compatible	No

## Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Input voltage limits	160...240 V
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	0.98

## Output

Maximum configurable power in W	24000 W
Harmonic distortion	Less than 3 %
Output frequency	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest factor	Unlimited
Wave type	Sine wave
Output voltage tolerance	+/- 5% static and 100% load step
Output harmonic distortion	< 2% linear load and < 4% non-linear load
Bypass type	Built-in maintenance bypass Built-in static bypass
Maximum configurable power in VA	30000 VA

## Conformance

Product certifications	cUL listed CSA UL 1778
Standards	CSA C22.2 No 107.1 ISO 14001 ISO 9001

## Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	55 dBA
heat dissipation	5896 Btu/h
NEMA degree of protection	NEMA 12
IP degree of protection	IP51

## Communications & Management

Preinstalled device	Network management card 2 with environmental monitoring
---------------------	---

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	164.3 cm
Package 1 Width	106.2 cm
Package 1 Length	65 cm
Package 1 Weight	660 kg

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

## Sustainability


**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

 Mercury Free

**Eu Rohs Directive**

Not applicable, out of EU RoHS legal scope

**California Proposition 65**

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)