

# Product data sheet

Specifications



## Emergency lighting Galaxy 300 30KVA 400V 3:3 CLA TT 60 min 15.6KW

G3H30KHT6AX710

⚠ Discontinued on: Aug 19, 2021

⚠ Discontinued - Service only

### Overview

Presentation	Three phase UPS for emergency lighting applications available in 3:1 and 3:3, 60 or 90 minute runtime options
Lead Time	Usually Ships within 2 Weeks

### Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated Power In W	15600 W
Rated Power In Va	30000 VA
Output Connector Type	Hard wire 5-wire (3P + N + E) 1
Battery Type	Lead-acid battery
Provided Equipment	User manual

### Batteries & Runtime

Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Additional Information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery Power In Vah	0 VAh runtime
Extended Runtime	0

### General

Product Web Sub-Family	Galaxy 300
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

### Physical

Height	130 cm
--------	--------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	50 cm
Depth	86 cm
Net Weight	200 kg
Mounting Preference	No preference
Usb Compatible	No

## Input

Network Frequency	45...65 Hz
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	323...437 V adjustable 380 V 340...460 V adjustable 400 V 357...477 V adjustable 415 V 340...460 V 400 V
Maximum Input Current	47 A
Switching Current Capacity	125 A
Input Harmonic Distortion	Less than 9 % for full load
Input Protection Type	GL fuse
Inrush Current	200 A peak
Load Power Factor	0.5 leading to 0.5 lagging

## Output

Maximum Configurable Power In W	24000 W
Harmonic Distortion	Less than 3 %
Output Frequency	50/60 Hz +/- 5 % sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest Factor	2.5 : 1
Wave Type	Sine wave
Output Voltage Tolerance	+/- 2% static and 100% load step
Output Harmonic Distortion	< 3% linear load and < 5% non-linear load
Output Overload Operation	60 seconds at 120% and 30 seconds at 145%
Required Output Current Protection	125 A
Bypass Type	Built-in maintenance bypass
Efficiency	93 % (full load) 92.7 % (half load)
Maximum Configurable Power In Va	30000 VA

## Conformance

Product Certifications	CE TÜV
Standards	EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 EN 61000-4-5 IEC 62040-2

## Environmental

Ambient Air Temperature For Operation	0...35 °C
Relative Humidity	0...95 %
Operating Altitude	0...30000 ft
Ambient Air Temperature For Storage	-10...60 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...9144.00 m
Acoustic Level	54.5 dBA
Heat Dissipation	1804 Btu/h
Ip Degree Of Protection	IP20

## Communications & Management

Free Slots	0
Preinstalled Device	Network management card
Control Panel	Multifunction LCD status and control console
Emergency Power Off	Yes

## Packing Units

Package 1 Height	144 cm
Package 1 Width	80 cm
Package 1 Length	96.5 cm
Package 1 Weight	226 kg

## Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

## Sustainability

**Green Premium™ label** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Under investigation

---