

Product datasheet

Specifications



MGE Galaxy 300 60kVA 400V 3:3, 0min Start-up 5x8

G3HT60KHLS

⚠ Discontinued on: 31 Dec 2019

⚠ End-of-service on: 18 Oct 2023

⚠ Discontinued

Overview

Presentation Effective three phase power protection against downtime and data loss for mission critical applications. UPS with long backup charger, supplied without batteries. To be used with external batteries. Please click here for additional runtime information

Lead Time Usually Ships within 2 Weeks

Main

Main Input Voltage 400 V 3 phases

Other Input Voltage 380 V
415 V

Main Output Voltage 400 V 3 phases

Other Output Voltage 380 V
415 V

Rated Power In W 54000 W

Rated Power In Va 60000 VA

Battery Type External battery system

Provided Equipment CD with software
Dust filter
Installation guide
Network management card
Start-up service
User manual

Batteries & Runtime

Efficiency [View Efficiency Graph](#)

Number Of Battery Filled Slots 0

Number Of Battery Free Slots 0

Additional Information kW/kVA = 0.9 PF with ambient temp up to 25°C. kW/kVA = 0.8 PF with ambient temp above 25°C

Battery Power In Vah 0 VAh runtime

Extended Runtime 0

General

Bypass Wiring Configuration 5 wire (3P + N + E)

Number Of Power Module Free Slots 0

Number Of Power Module Filled Slots 0

Redundant	No
-----------	----

Physical

Height	190 cm
Width	70 cm
Depth	95 cm
Net Weight	375 kg
Mounting Preference	No preference
Usb Compatible	No

Input

Network Frequency	45...65 Hz
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	323...437 V adjustable 380 V 340...460 V adjustable 400 V 357...477 V adjustable 415 V 340...477 V
Maximum Input Current	228 A
Switching Current Capacity	160 A
Max Short Time Withstand Current	16 kA
Input Harmonic Distortion	Less than 5 % for full load
Input Protection Type	3-pole circuit breaker
Inrush Current	200 A peak
Load Power Factor	0.5 leading to 0.5 lagging
Input Power Factor At Full Load	0.99

Output

Maximum Configurable Power In W	54000 W
Harmonic Distortion	Less than 5 %
Output Frequency	50/60 Hz +/- 5 % sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Crest Factor	3 : 1
Output Voltage Tolerance	+/- 2% static and 100% load step
Output Harmonic Distortion	< 3% linear load and < 5% non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Required Output Current Protection	160 A
Neutral Output Current	87 A
Bypass Type	Built-in static bypass
Maximum Configurable Power In Va	60000 VA

Conformance

Product Certifications	CE EAC
------------------------	-----------

Standards	EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 ISTA 2B IEC 62040-4
------------------	--

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0.00...4572.00 m
Acoustic Level	65 dBA
Ip Degree Of Protection	IP20

Communications & Management

Preinstalled Device	Network management card
Control Panel	Multifunction LCD status and control console
Emergency Power Off	Yes

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	197.8 cm
Package 1 Width	112 cm
Package 1 Length	82.4 cm
Package 1 Weight	395 kg

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
-----------------	---

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

Eu Rohs Directive

Will be compliant – Date to be confirmed

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)
