

Product data sheet

Specifications



MGE Galaxy 5500 30kVA 400V Integrated Parallel UPS, Start-up 5x8

G55TUPSM30HINS

- !

Discontinued on: 05 July 2021
- !

End-of-service on: 18 October 2023

! Discontinued

Overview

Presentation	A versatile 3-phase UPS for facility, industrial and data center applications. Configurable system with a comprehensive range of accessories to meet your application demands.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	27000 W
Rated power in VA	30000 VA
Output connector type	Hard wire 4-wire (3P + N) 1
Battery type	External battery system
Provided equipment	Installation guide Network management card Start-up service User manual

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery power in VAH	0 VAh runtime
Extended runtime	0

General

Bypass voltage tolerance	+/- 10 % settable from +/- 4/6/8 and 10 %
Max bypass input current	43 A
Number of power module free slots	0

Number of power module filled slots	0
-------------------------------------	---

Redundant	No
-----------	----

Physical

Height	190 cm
--------	--------

Width	71.2 cm
-------	---------

Depth	85.5 cm
-------	---------

Net weight	400 kg
------------	--------

Mounting preference	No preference
---------------------	---------------

USB compatible	No
----------------	----

Input

Network frequency	45...65 Hz
-------------------	------------

Input voltage limits	323...437 V 380 V 340...460 V 400 V 353...477 V 415 V
----------------------	---

Maximum input current	60 A
-----------------------	------

Switching current capacity	125 A
----------------------------	-------

Max short time withstand current	20 kA
----------------------------------	-------

Input harmonic distortion	Less than 3 % for full load
---------------------------	-----------------------------

Input protection type	GL fuse
-----------------------	---------

Load power factor	0.9
-------------------	-----

Input Power Factor at Full Load	1
---------------------------------	---

Output

Maximum configurable power in W	27000 W
---------------------------------	---------

Harmonic distortion	Less than 2 %
---------------------	---------------

Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
------------------	--

Crest factor	3 : 1
--------------	-------

Wave type	Sine wave
-----------	-----------

Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
--------------------------	--

Output harmonic distortion	< 1% linear load and < 2.5% non-linear load
----------------------------	---

Output overload operation	10 minutes at 125% and 60 seconds at 150%
---------------------------	---

Required output current protection	43 A
------------------------------------	------

Neutral output current	65 A
------------------------	------

Bypass type	Built-in maintenance bypass Built-in static bypass Optional external bypass
-------------	---

Efficiency	94 % (full load)
------------	------------------

Maximum output current	190 A
------------------------	-------

Maximum configurable power in VA	30000 VA
----------------------------------	----------

Conformance

Product certifications	CE TÜV VDE
Standards	IEC 62040-1-2 EN/IEC 62040-2 EN/IEC 62040-3 ISO 9001

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-20...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...9753.60 m
Acoustic level	55 dBA
Heat dissipation	6928 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	2
Preinstalled device	Network management card 2 with environmental monitoring, out of band access and Modbus
Control panel	Multifunction LCD status and control console
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203 cm
Package 1 Width	96 cm
Package 1 Length	98 cm
Package 1 Weight	420 kg

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up, 1 year (parts only)
----------	--

Recommended replacement(s)

G55TUPSM30HINS is replaced by the following product range:



Galaxy VS
High-efficiency, modular 10-150 kW 3-phase UPS with eConversion for edge, small, and medium data centers and business-critical applications. Optimize TCO with Galaxy Lithium-ion battery options.

